

tritium acam b801

Features:

- Advanced DPS(Digital Pixel System) Technology
- No Smear and Minimum blooming problem
- Strong capability to catch full clean picture under back light or extreme lighting environment.
- CS mount or C mount with 5mm adaptor ring lens
- 480 TV lines
- Suitable for surveillance of lobby entrance / ATM / Car Plate Identification
- Full O.S.D.(On-Screen-Display) menu for multiple functions

<p style="text-align: center;"><u>Camera Specification:</u></p> <p>Sensor: 1/3" COLOUR DPS SENSOR BLC: *SEE EXPOSURE MODE* Resolution: PAL: 720(H)X540(V) Horizontal Resolution: 480 TV LINES Sync System: INTERNAL SYNC. LINE-LOCK(AC INPUT REQUIRED) S/N Ratio: OVER 48db AGC: ON/OFF SWITCH Min. Illumination: 1.0 LUX / F1.2 Exposure Mode: 5 MODES SELECTABLE ON SCREEN INDOOR MODE OUTDOOR MODE FLOUR MODE BACKLIGHT MODE USER MODE Slow Shutter: ON/OFF LEVEL 2~32 Camera ID Symbol: 12 CHARACTER TITLE GENERATOR</p>
<p style="text-align: center;"><u>Lens:</u></p> <p>Lens Mount: CS MOUNT OR C MOUNT WITH 5mm ADAPTOR RING LENS IRIS Level: DIRECT DRIVE A.I. ONLY D/D Lens IRIS Level: LEVEL: -34~20</p>
<p style="text-align: center;"><u>Audio:</u></p> <p>Audio: N/A</p>
<p style="text-align: center;"><u>Display:</u></p> <p>Video Output: 1.0Vp-p, 75Ω S-Video: MINI DIM S-VIDEO, Y:1.0Vp-p, 75Ω C:286mV, 75Ω (NTSC) C:330mV, 75Ω (PAL)</p>
<p style="text-align: center;"><u>Networking:</u></p> <p>Operation: N/A</p>
<p style="text-align: center;"><u>Electrical:</u></p> <p>POWER SOURCE: DC 12V / AC 24V LINE LOCK. CONSUMPTION: 7W MAX.</p>
<p style="text-align: center;"><u>Environmental:</u></p> <p>Working Temperature: 0°C TO +40°C</p>
<p style="text-align: center;"><u>Physical:</u></p> <p>Waterproofing Criterion: Dimension: 60(W)x 50(H)x 118(D)mm Weight: APPROX. 370g.</p>